



Neutra Sul®

Professional Grade Oxidizer

Protects against irregular coloring and smells in treated water.

Pro Neutra Sul® is formulated to remove pollutants from any water supply through oxidation. Neutra Sul should be used in replace of Hydrogen Peroxide 7% solution to prevent the formation of colors, tastes, corrosion and scaling by pollution degradation.

Available in 1 and 2.5 gallon sizes.

Applications

Oxidation - Normal procedure for oxidizing a water supply is usually specified by the chemical feed pump manufacturer or supplier and depends on water conditions. There are many types, designs and methods of introducing Neutra Sul to the water supply. A normal method is to inject Neutra Sul directly into the water line with the use of a chemical feed pump. Dosage rates will vary. If unsure consult owner's manual.

Dosage - Proper dosage rates will vary depending on application. For oxidation of impurities, feed Neutra Sul until there are very few oxygen bubbles in treated water. 10 oz. per 100 gallons of water will sanitize a system at 50 ppm of Neutra Sul.



Benefits to the User

- No odor
- Non flammable
- Decomposes into oxygen and water
- More powerful oxidant than chlorine and Potassium Permanganate

Technical Information

Pro Neutra Sul is a clear, chemically stable, liquid. Neutra Sul is formulated with Hydrogen Peroxide. Do not mix with other chemicals.

Part #	Size	Qty.
HP41N	1 gal.	4
HP22N	2.5 gal	2